



BTD70WH

Dimensions (mm)	External	Internal
Height	2000	
Width	685	
Depth	660	
Capacity (ltr)		
Gross		240
Net		190



BTD100WH

Dimensions (mm)	External	Internal
Height	2000	
Width	1000	
Depth	660	
Capacity (ltr)		
Gross		360
Net		290



BTD130WH

Dimensions (mm)	External	Internal
Height	2000	
Width	1310	
Depth	660	
Capacity (ltr)		
Gross		470
Net		375



BTD150WH

Dimensions (mm)	External	Internal
Height	2000	
Width	1500	
Depth	660	
Capacity (ltr)		
Gross		540
Net		430



BTD200WH

Dimensions (mm)	External	Internal
Height	2000	
Width	1935	
Depth	660	
Capacity (ltr)		
Gross		720
Net		575

Features

- White laminated exterior & interior
- 4 heavy duty adjustable shelves (300mm deep) with pricing strips
- Condenser over temperature audible alarm
- Adjustable feet
- Night blind fitted as standard
- Internal illumination - LED lighting to each shelf
- Tempered glass side panels
- Clear acrylic shelf edge risers

Additional Extras


- B9-SHELF70W - Shelf for BTD70WH (inc brackets)
- B9-SHELF100W - Shelf for BTD100WH (inc brackets)
- B9-SHELF130W - Shelf for BTD130WH (inc brackets)
- B9-SHELF150W - Shelf for BTD150WH (inc brackets)
- B9-SHELF200W - Shelf for BTD200WH (inc brackets)




Technical Specification

	BTD70WH	BTD100WH	BTD130WH	BTD150WH	BTD200WH
Temperature Range	+2°C ~ +10°C	+2°C ~ +10°C	+2°C ~ +10°C	+2°C ~ +10°C	+2°C ~ +10°C
Climate Class	3	3	3	3	3
Power Supply	2x 13amp	2x 13amp	2x 13amp	2x 13amp	2x 13amp
Cooling	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Defrost	Automatic	Automatic	Automatic	Automatic	Automatic
Noise Level	65db	65db	65db	65db	65db
Refrigerant	R290	R290	R290	R290	R290
Energy Efficiency Class	G	F	F	F	F
Energy Consumption (kw/24hrs)	11.04	12.96	21.92	23.40	25.18
Power Usage (w)	1104	1296	2195	2340	2518
Weight (kg)	187	225	272	310	370


BTD70WH




BTD100WH



BTD130WH



BTD150WH



BTD200WH

